

STANDARD CONFIGURATIONS

PROCON™ Junior	1 to 4 channels
----------------	-----------------

OPTICAL

Type	Single mode (SM), multimode (MM) or hybrid
Transmission	10Gbit/s
Insertion loss (SM)	Typical Insertion Loss -1,0dB (1310 nm) Maximum Insertion Loss -1,5dB (1310 nm)
Insertion loss (MM)	Typical Insertion Loss -1,0dB (1300 nm) Maximum Insertion Loss -1,5dB (1300 nm)
Return loss (PDL)	>35dB at 1310nm or 1550nm Polarization dependent loss less than 0,5dB

MECHANICAL

Coupling type	Hermaphroditic
Compliant	ROHS & REACH
Material	Hard anodized aluminum (MIL-A-8625 TYPE III CLASS 2)
Alternative material	Marine bronze, stainless steel or titanium
Colour	Grey
Durability	3000 mating cycles (MIL-DTL-83526)
Free fall	500 falls from 1,2 meters height (IEC 68-2-32-P II)
Vibration	5-500Hz, 0,75mm amplitude at 10G
Shaking	390 m/S numbers of shakes 3x4000
Shock pulse length	11ms, half sine at 35g Numbers of axis: 3 (x, y, z)
Recommended wall thickness	2-3 mm - not valid for cable plug JR and Mini

ENVIRONMENTAL

Operating temperature	-57°C to +85°C,
Water immersion	IP67
Air pressure	<25kPa -55°C during 4h
Corrosion resistance	500h salt spray
Flammability	DOD-STD-1678, method 5010

V2.2, 2025-10-14



MORE INFORMATION